

# NWERC 2025 Test Session

Solutions presentation

November 29, 2025



## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.



## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.

## Naive solution

Do something stupid.  $\mathcal{O}(2^n)$  is too slow!

## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.

## Naive solution

Do something stupid.  $\mathcal{O}(2^n)$  is too slow!

## Solution

Instead, just compute the answer. Run time:  $\mathcal{O}(1)$ .

## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.

## Naive solution

Do something stupid.  $\mathcal{O}(2^n)$  is too slow!

## Solution

Instead, just compute the answer. Run time:  $\mathcal{O}(1)$ .

Statistics: ... submissions, ... accepted, ... unknown

# B: Build Dependencies

Jeroen Bransen

## Problem

Find a satisfying build order.



## Problem

Find a satisfying build order.

## Solution

Topological sorting, for example with DFS, leading to a solution with running time  $\mathcal{O}(n)$ .

## Problem

Find a satisfying build order.

## Solution

Topological sorting, for example with DFS, leading to a solution with running time  $\mathcal{O}(n)$ .

Statistics: ... submissions, ... accepted, ... unknown



## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.



## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.

## Naive solution

Do something stupid.  $\mathcal{O}(2^n)$  is too slow!

## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.

## Naive solution

Do something stupid.  $\mathcal{O}(2^n)$  is too slow!

## Solution

Instead, just compute the answer. Run time:  $\mathcal{O}(1)$ .

## Problem

Print  $4\sqrt{n}$  with sufficiently many digits.

## Naive solution

Do something stupid.  $\mathcal{O}(2^n)$  is too slow!

## Solution

Instead, just compute the answer. Run time:  $\mathcal{O}(1)$ .

Statistics: ... submissions, ... accepted, ... unknown